

TKX-T927- SIP : Regular

TKX-T927- SIP: Include IP Camera



Hardware :

- 2 to 8 configurable push buttons inputs (or sensors)
- Telephone 3x4 keypad
- Speaker out (low impedance)
- Line out (high impedance)
- 2 Ethernet ports
- 9~24 Vdc or PoE powered
- 2 Wiegand interfaces (1 TTL RS-232)
- Power on led
- Status led (software controlled)

- 3 external for signaling
- 2 relays configurable NO/NC

Functions :

- GUI english, spanish & portuguese
- Full IP SIP device
- Registrates as extension of IP PBX or works standalone with direct IP Address calls
- Unicast / Multicast
- Prerecorded messages
- Access Control standalone or client
- Server: PIN, Proximity Card, Fingerprint
- Notify / HTTP commands for relays activating
- QR decoding
- Echo cancellation

Protocol :

TCP/IP, SIP, G.711 / G.729, Opus (rcvonly), MySQL, HTTP, RTSP, RTP, FTTP, Syslog, SNTP, SNMP, DHCP

Camera :

- 1080P PCB IP Camera module, 1 board, power and internet (Optional USB interface, audio in/out, reset)
- 1/2.8"2.0Megapixels Progressive Scan Sony 323CMOS
- Hisilicon Hi3516C
- Max25/30fps@2.0Megapixels (1920x1080, 1280x960, 1280x720)
- H.264 & MJPEG, double stream
- Support Onvif 2.4protocol
- 0. 1Lux/F1.2 (Color), 0.01Lux/F1.2(B/W)
- Working Environment -20°C~+60°C , Less than 90% RH



C/ Can Pantiquet, 81
08100 Mollet del Vallés

Tel: +34 935702623
Fax: +34 935792185

info@netaselcom.com
www.netaselcom.com